

# SXJS3019

## Resepsiyon Lift (Ultra Zarif Makas Lift)



- 110 mm profil yüksekliđi ve zemin üstü montaj
- Platform uzunluđu 1430 mm, açılır rampa ile uzunluđu 2000 mm
- Makas kolları uluslararası standartlarda Q345 sert çeliktir.
- Daha sağlam ve daha güvenli çift devreli tasarım
- Maksimum yükseklik 1900mm
- Kontrol sisteminde baskı PCB ve Siemens elektrik parçaları kullanılır
- Ürün hızlı tamir, bakım, ön kontrol ve kısa şasi olan araçlara uygun bir şekilde tasarlanmıştır
- Ultra zarif tasarım size yer kazandırır ve rampa çıkışı daha pratik olur.

### Teknik Özellikler:

- Makas sac kalınlığı 30 mm
- Platform sac kalınlığı 6 mm
- Yük kapasitesi: 3000 kg
- Kaldırma yüksekliđi: 1900 mm
- Sistem basıncı: 25 Mpa
- Pnömatik basınç: 0,4-0,8 Mpa
- Ağırlık: 880 kg
- Minimum yükseklik: 110 mm
- Platform uzunluđu: 1430-2000 mm
- Motor gücü: 3 kW
- Besleme gerilimi: 380/220 V



Type	Lifting capacity	Lifting height	System pressure	Pressure pneumatic	Motor power	Voltage	N.W	MIN. Height	Platform Length
SXJS3019	3.0T	1900mm	25Mpa	0.4-0.8Mpa	3KW	380/220V	0.88T	110mm	1430-2000mm
	7700LB	74inch					1940LB	4inch	56-78inch

### Feature:

- Minimum height is only 110 mm, suitable for on ground installation
- Main platform length is 1430 mm, extended up to 2000 mm
- Scissor arms use International Standard solid steel Q345 , permanent deformation
- Dual-circuit design, more stable and secure
- Maximum height is 1900 mm, dedicated increased shelf optional, meet different customer needs
- Control system use printing PCB and Siemens electrical parts, stable performance
- The overall design is very suitable for fast repair maintenance, pref light and luxury low chassis vehicles
- dedicated increased shelf optional, convenient for lifting high chassis vehicles
- Ultra thin design ,save space for customers, more beautiful and practical
- Driving on ramp
- Scissor's sheet iron thickness is 30 mm
- Platform's sheet iron thickness is 6 mm